



CS-U10

CatScope

Technical Specifications of CS-U10

Head	Seidentopf Binocular Head, Inclined at 45° and 360° rotatable Interpupillary Distance adjustment range: 48 - 75mm Diopter Adjustment: $\pm 5^\circ$
Eyepiece	WF 10X/18mm
Nosepiece	Quadruple, Forkward tilted, Click-stop Revolving mechanism with multiple ball bearing
Objectives	Anti-fungal Achromatic Color-coded DIN Objectives 4X, 10X, 40X(Spring), 100X(Spring, Oil)
Stage	Double Layer Mechanical Stage, Stage size: 120 x 120mm Movement range: 60mm x 30mm controlled with a left hand stage handle
Condenser	1.25 N.A. Abbe Condenser with Aperture Iris diaphragm
Focusing	Stage height movement with Coaxial Coarse and Fine Focusing Adjustment Knob by Rack & Pinion Mechanism. Coarse Stroke range 30mm. Fine focusing interval: 2 μ m
Illumination	Halogen Illumination 6V-15W with Adjustable brightness
Power supply	85V-265V Universal Power Supply
Warranty	One year against any manufacturing defects. No warranty on consumables

Options in-lieu of mentioned standard specification:

- » Monocular Head
- » LED Illumination

Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer.
Copyright © CATALYST BIOTECH. PLEASE READ THE CORRESPONDING MANUALS CAREFULLY BEFORE USING YOUR EQUIPMENT.



Catalyst Biotech

C-302, Third Floor, Anupam CHS Ltd.
Plot No.: 79, Panvel - 410 206.
Maharashtra - India.
E-mail : catalyst@catalystbiotech.com
Website : www.catalystbiotech.com

Our Authorised Distributor :

